

MATERIAL SAFETY DATA SHEET

for
Crushed Limestone



Effective Date: August 2001
Page 1 of 4

1. PRODUCT/COMPANY IDENTIFICATION

Manufacturer's Name & Address:

Titan Florida
11000 NW 121 Way
Medley, FL 33178

Trade Name:

Crushed Limestone

Chemical Name and Synonyms:

Natural Limestone (calcium carbonate) or Gravel, Construction Aggregate, Crushed Stone*

Telephone Number for Information:

1.800.458.4250

Department of Transportation Identification No.:

None

Emergency Telephone:

1.800.965.9896

*Composition varies naturally, typically contains crystalline silica

2. COMPOSITION INFORMATION

<u>Chemical Name</u>	<u>CAS Registry Number</u>	<u>% in this cement product</u>
Calcium carbonate or gravel*	1317-65-3	60-95
*May contain crystalline silica	14808-60-7	>1

3. PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	N/A
Specific Gravity (H ₂ O = 1)	1.7-3.0
Vapor Pressure (mm Hg)	N/A
Melting Point	N/A
Vapor Density (AIR-1)	N/A
Evaporation Rate	N/A
Solubility in Water	Negligible
Appearance & Odor	Gray, solid mixture; faint odor

4. FIRE AND EXPLOSION HAZARD DATA

Flash Point	N/A
Extinguishing Media	N/A
Special Fire Fighting Procedures	None
Unusual Fire & Explosion Hazards	None
Flammable Limits	N/A
LEL	N/A
UEL	N/A

MATERIAL SAFETY DATA SHEET

for Crushed Limestone



Page 2 of 4

5. REACTIVITY DATA

- Stability:** Stable. Avoid contact with incompatible materials.
- Incompatibility:** Will react with strong acids.
- Hazardous Decomposition or Byproducts:** Will not spontaneously occur. Respirable dust particles may occur from handling dry material.
- Hazardous Polymerization:** Will not occur. No conditions to avoid.

6. HEALTH HAZARD DATA AND FIRST AID

EXPOSURE LIMITS:

Unless specified otherwise, limits are expressed as a time-weighted average (TWA) concentration for an 8-hour work shift of a 40-hour workweek. Limits for cristobalite and tridymite (other forms of crystalline silica) are equal to one-half the limits for quartz.

ABBREVIATIONS:

ACGIH TLV: Threshold limit value of the American Conference of Governmental Industrial Hygienists (ACGIH).

mg/m³: Milligrams of substance per cubic meter of air.

NIOSH REL: Recommended exposure limit of the National Institute for Occupational Safety and Health (NIOSH).

OSHA PEL: Permissible exposure limit of the federal Occupational Safety and Health Administration (OSHA), expressed as a time weighted average (TWA) concentration for an 8-hour work-day and a 40-hour workweek.

Calcium Carbonate: OSHA PEL (respirable fraction) 5 mg/m³, (total dust) 15 mg/m³, ACGIH TLV (total dust) 10 mg/m³, NIOSH REL (respirable) 5 mg/m³, (total) 10 mg/m³.

Crystalline Silica SiO₂: OSHA PEL (respirable) [10 mg/m³ ÷ (% SiO₂+2)], (total dust) [30 mg/m³ ÷ (% SiO₂+2)], ACGIH TLV (respirable) 0.05 mg/m³, NIOSH REL (respirable) 0.05 mg/m³.

Other Particulates: OSHA PEL (total particulate, not otherwise regulated) 15 mg/m³, (respirable particulate, not otherwise regulated) 5 mg/m³, ACGIH TLV (nuisance particulates) 10 mg/m³ (inhalable), 5 mg/m³ (respirable).

HEALTH HAZARDS:

Primary Route(s) of Entry:

Inhalation: Yes

Skin: No

Ingestion: No

Acute:

Eye Contact: Direct contact with dust may cause irritation by mechanical abrasion. Exposure to wet material may be slightly caustic and cause irritation or injury.

Skin Contact: Direct contact with dust may cause irritation by mechanical abrasion. Exposure to wet material may be slightly caustic and cause irritation or injury.

Skin Absorption: Not expected to be a significant exposure route.

Ingestion: If ingested, the material may become slightly caustic and cause tissue irritation. Ingestion of large amounts may cause gastrointestinal irritation and blockage.

Inhalation: Dusts may irritate the nose, throat, and respiratory tract. Coughing, sneezing, and shortness of breath may occur following exposures in excess of appropriate exposure limits.

Chronic:

Inhalation: Chronic exposure to respirable dust in excess of appropriate exposure limits may cause lung disease. Silicosis may result from excessive exposure to respirable silica dust for prolonged periods. Not all individuals with silicosis will exhibit symptoms. Silicosis is progressive and symptoms can appear at any time, even after exposure has ceased. Symptoms may include shortness of breath, coughing, or right heart enlargement and/or failure. Persons with silicosis have an increased risk of pulmonary tuberculosis infection. Tobacco smoking may increase the risk of developing lung disorders, including emphysema and lung cancer.

MATERIAL SAFETY DATA SHEET

for Crushed Limestone



Page 3 of 4

Carcinogenicity: Crushed limestone is not listed as a carcinogen by the National Toxicology Program (NTP), OSHA or the International Agency for Research on Cancer (IARC). However, crystalline silica is classified by IARC as a carcinogenic to humans (Group 1). The NTP has characterized respirable silica as "known to be a human carcinogen". Prolonged and repeated breathing of silica may cause lung cancer.

Signs & Symptoms of Exposure: Irritation of eyes, skin and/or respiratory system.

Medical Conditions Generally Aggravated by Exposure: Inhaling respirable dust may aggravate existing respiratory system disease(s) and/or dysfunctions such as emphysema or asthma. Exposure may aggravate existing skin and/or eye conditions.

EMERGENCY & FIRST AID PROCEDURES:

- Eyes:** Immediately flush eye(s) with plenty of clean water for at least 15 minutes, while holding the eyelid(s) open. Beyond flushing, do not attempt to remove material from the eye(s). Contact a physician if irritation persists or later develops.
- Skin:** Wash skin with cool water and pH-neutral soap or mild detergent intended for use on skin. Seek medical treatment if irritation persists or later develops.
- Ingestion:** If person is conscious, give large quantity of water and induce vomiting; however, never attempt to make an unconscious person drink or vomit. Get immediate medical attention.
- Inhalation:** Remove to fresh air. Dust in throat and nasal passages should clear spontaneously. Contact a physician if irritation persists or later develops.

7. PERSONAL PROTECTION AND CONTROL MEASURES

- Ventilation:** Local exhaust or general ventilation adequate to maintain exposures below appropriate exposure limits.
- Other:** Dust and silica levels should be monitored regularly. Dust and silica levels in excess of appropriate exposure limits should be reduced by all feasible engineering controls, including (but not limited to) wet suppression, ventilation, process enclosure, and enclosed employee work stations.
- Respiratory Protection:** When dust or silica levels exceed or are likely to exceed appropriate exposure limits, follow MSHA or OSHA regulations, as appropriate, for use of NIOSH-approved respiratory protection equipment.
- Skin Protection:** Protective gloves, shoes and protective clothing should be worn to avoid contact with skin.
- Eye Protection:** Safety glasses with side shields should be worn as minimum protection. Dust goggles should be worn when excessive (visible) dust conditions are present or anticipated. Contact lenses should not be worn when working with this product.
- Hygiene:** Periodically wash exposed skin with a pH-neutral soap. Wash again before eating, drinking, smoking, and using toilet facilities. Wash work clothes after each use.

8. STORAGE AND HANDLING PRECAUTIONS

Respirable silica and dust may be generated during crushing, processing, handling and storage when hardened product is subjected to mechanical forces. The personal protection and controls identified in Section VII of the MSDS should be applied as appropriate.

Do not store or handle near food and beverages or smoking materials.

MATERIAL SAFETY DATA SHEET

for Crushed Limestone



Page 4 of 4

9. SPILL, LEAK AND DISPOSAL PRACTICES

The personal protection and controls identified in Section VII of the MSDS should be applied as appropriate.

Steps to Be Taken if Material Is Released or Spilled: Spilled materials, where dust can be generated, may overexpose cleanup personnel to respirable silica and dust. Wetting of spilled material and/or use of respiratory protective equipment may be necessary. Do not dry sweep spilled material.

Waste Disposal Method: Dispose of waste materials only in accordance with applicable federal, state, and local laws and regulations.

NOTICE: Based on research of available data, Titan Florida believes that the information contained in this Material Safety Data Sheet is accurate. The suggested procedures are based on data and experience as of the date of preparation of the MSDS. The suggestions should not be confused with nor followed in violation of applicable laws, regulations, rules or insurance requirements. Titan Florida's voluntary preparation of this MSDS should not be construed, in any way, as an agreement to be subject to MSHA/OSHA jurisdiction, as applicable.